



## **EDIsecure**® DCP 350 Direct Card Printer

### A HIGH-PERFORMANCE, SINGLE- AND/OR DOUBLE-SIDE PRINTER FOR YOUR GROWING NEEDS

- Single- and/or Double-side printed cards in brilliant color with crisp, sharp graphics
- Complete modularity due to upgradable options
- Competitive printing performance with a wide ribbon selection
- Optional lamination module for the *EDIsecure*® DCP 350 dual-side printer version with different types of patch lamination materials incl. holographic patches
- Convenient, automatic front card loading and output
- User-friendly design for easy operation and maintenance
- Advanced cleaning roller system
- LCD display with 2 LED buttons
- The perfect solution for all kinds of applications whether a photo is printed or not

The very competitive single- and/or double-side, edge-to-edge *EDIsecure*® DCP 350 Direct Card Printer is the perfect solution for all kinds of applications whether a photo is printed or not. With its attractive design and sturdy construction, the *EDIsecure*® DCP 350 produces high quality, professional looking ID cards and fits perfectly on any desk.

The *EDIsecure*® DCP 350 operator-friendly design has a front-facing card feeder and output hopper plus reloadable ribbon cartridges for easy handling of supplies. The *EDIsecure*® DCP 350 offers a great variety of encoding options such as contact chip, contactless chip and magnetic stripe, and is available with an Ethernet interface. With its modular assembly, the standard single-side printer can be easily upgraded to a dual-side printer with an optional available lamination module.

Your initial investment is well protected by its compact yet modular design and variety of available options, which eliminates the need to purchase a new system every time your printing requirements change.



THERE IS ONE FOR EVERYBODY



## FEATURES

- Wide selection of ribbon types
- Front-facing, automatic card feeder and output hopper
- High capacity monochrome ribbons
- Quick ribbon change, with easy to use cartridges
- Operator replaceable printheads
- Advanced cleaning roller system to avoid scratches on cards
- Automatic ribbon detection and low ribbon warning
- Audible and visual message prompts
- LCD display with 2 LED buttons

## UPGRADABLE OPTIONS

- Magnetic stripe encoding (3 Track HiCo & LoCo)
- IC (Contact) Encoding
- Contactless (Internal & External) Encoding
- Flipper Module for dual-side printing
- Dual-side Lamination Module with various types of laminates
- Ethernet

## PRO SUPPLIES

<b>Y M C K OP</b>	250 cards/ribbon (c/r)
<b>Y M C K OP K</b>	200 cards/ribbon (c/r)
<b>Y M C K OP</b>	350 cards/ribbon (c/r)
<b>Y M C UV K OP</b>	200 cards/ribbon (c/r)

## PRO MONOCHROME SUPPLIES

<b>SILVER</b>	1200 cards/ribbon (c/r)
<b>GOLD</b>	1200 cards/ribbon (c/r)
<b>CARBON BLACK</b>	1200 cards/ribbon (c/r)
<b>CARBON BLACK</b> <b>OP</b>	600 cards/ribbon (c/r)
<b>WHITE</b>	1200 cards/ribbon (c/r)
<b>BLUE</b>	1200 cards/ribbon (c/r)
<b>RED</b>	1200 cards/ribbon (c/r)
<b>SCRATCH-OFF</b>	1200 cards/ribbon (c/r)

## SUPPLIES

<b>Y M C K OP</b>	250 cards/ribbon (c/r)
<b>Y M C K OP K</b>	200 cards/ribbon (c/r)
<b>Y M C K UV OP</b>	200 cards/ribbon (c/r)
<b>K OP</b>	600 cards/ribbon (c/r)
<b>CARBON BLACK</b>	1200 cards/ribbon (c/r)

## SPECIFICATIONS OF EDIsecure® DCP 350

<b>Print Method</b>	Color dye-sublimation and monochrome thermal transfer
<b>Print Mode</b>	Single- and/or double-side edge-to-edge direct card printing
<b>Print Speed</b>	Full color: up to 144 cards per hour (single-side) Monochrome: up to 720 cards per hour (single-side)
<b>Print Resolution</b>	300 dpi
<b>Print Head</b>	Operator replaceable, 24 month warranty, no count limitation using EDIsecure® Cards
<b>Card Types</b>	All PVC and Composite PVC Cards of ISO ID-1/CR-80 size, 85.60 x 53.98 mm
<b>Card Thickness</b>	0.3 – 1.0 mm
<b>Input Hopper Capacity</b>	100 cards (0.76 mm)
<b>Output Hopper Capacity</b>	40 cards (0.76 mm)
<b>Interface</b>	USB and optional Ethernet
<b>Operating System Support</b>	Windows 2000, Windows XP, Windows Vista Windows 7 (32 & 64 Bit)
<b>Printer Dimensions (WxLxH)</b>	Single: 170 x 420 x 195 mm (6.7" x 16.5" x 7.7" in.) Double: 170 x 510 x 195 mm (6.7" x 20" x 7.7" in.) Lamination: 170 x 900 x 195 mm (6.7" x 35" x 7.7" in.)
<b>Weight</b>	Approx. 5 - 9 kg (11 - 20 lbs.)
<b>Power Supply</b>	100/120 V and 220/240 V, 50/60 Hz FCC, CE, UL, GOST-R, and CCC approved, 45W

Digital Identification Solutions AG  
Germany  
Phone: + 49 711 341 689 - 0  
Email: mail@edisecure.com

Matica System S.p.a.  
Italy  
Phone: + 39 02 922 72501  
Email: info@maticasystem.com

Digital Identification Solutions Pte. Ltd.  
Singapore  
Phone: + 65 6352 8364  
Email: mail@sg.edisecure.com

Digital Identification Solutions (Beijing) Co. Ltd.  
P.R. China  
Phone: + 86 10 6437 4376  
Email: mail@cn.edisecure.com

Digital Identification Solutions (Branch)  
Dubai, United Arab Emirates  
Phone: + 971 4 299 4146  
Email: mail@uae.edisecure.com

Digital Identification Solutions S. de R.L. de C.V.  
México  
Phone: + 52 442 2171 768 - 0  
Email: mail@mx.edisecure.com

Digital Identification Solutions LLC  
United States of America  
Phone: + 1 864 272 1199  
Email: mail@us.edisecure.com

www.edisecure.com